follows:

"SUBSECTION 414.13 SEPARATION BY BREEZEWAY. PRIVATE GARAGES ATTACHED TO ONE (1) AND TWO (2) FAMILY DWELLINGS SHALL BE PROTECTED AS REQUIRED IN SECTION 414.11. SUCH GARAGES SEPARATED FROM RESIDENCE OUTSIDE THE FIRE LIMITS BY A BREEZEWAY NOT LESS THAN TEN FEET (10') IN LENGTH MAY BE OF UNPROTECTED FRAME (TYPE 4-B) CONSTRUCTION BUT THE JUNCTION OF THE GARAGE AND BREEZEWAY SHALL BE FIRESTOPPED TO COMPLY WITH SECTION 876.0."

- (18) Strike all of Subsection 425.0.
- (19) Strike all of Subsection 429.52 and insert new Subsection 429.52 in lieu thereof, to stand in the place and stead of the section so stricken, and to read as follows:
- "FOR WALL SLOPES TO A DEPTH UP TO FIVE FEET (5') FROM THE TOP, THE WALL SLOPE SHALL NOT BE MORE THAN ONE FOOT (1') HORIZONTAL IN FIVE FEET (5') VERTICAL."
- (20) Strike all of Subsection 429.53 and insert new Subsection 429.53 in lieu thereof, to stand in the place and stead of the section so stricken, and to read as follows:

"THE SLOPE OF THE FLOOR ON THE SHALLOW SIDE OF THE TRANSITION POINT SHALL NOT EXCEED ONE FOOT (1') VERTICAL TO TWELVE FEET (12') HORIZONTAL. THE TRANSITION POINT BETWEEN SHALLOW AND DEEP WATER SHALL BE BETWEEN THE 3-1/2' TO 4-1/2' DEPTH. THE SLOPE RATION FOR THE BOTTOM OF THE DEEP END SHALL NOT EXCEED ONE FOOT (1') VERTICAL TO THREE FEET (3') HORIZONTAL."

(21) Strike all of Subsection 429.62 and insert new Subsection 429.62 in lieu thereof, to stand in the place and stead of the subsection so stricken, and to read as follows:

"PUBLIC AND SEMI-PUBLIC SWIMMING POOLS SHALL BE DESIGNED AND INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF THE MARYLAND STATE DEPARTMENT OF HEALTH REGULATIONS. THE PERTINENT PORTION OF THESE REGULATIONS IS COVERED IN REGULATIONS 43L04, ENTITLED 'REGULATIONS GOVERNING PUBLIC SWIMMING POOLS AND BATHING BEACHES'. PLANS AND SPECIFICATIONS FOR POOLS AND THE APPURTENANCES THEREOF MUST RECEIVE THE WRITTEN